



# OPERATING INSTRUCTIONS AND PARTS LIST



**FILE COPY**  
Return to Engineering Dept.


0611-213

Printed in U.S.A.

959

**YARD-MAN** Incorporated 1410 W. Ganson St., Jackson, Michigan

BUILDERS OF THE ORIGINAL SILENT YARD-MAN LAWN MOWER



## SERVICE

1. Sharpening is required when the mower will not cut satisfactorily without the reel blades wiping on the cutter bar.

2. Most lawn mower service shops are equipped with Yard-Man factory-built service equipment to give your YARD-MAN the same precision it had when it came from the Yard-Man factory.

## HOW TO ORDER REPAIR PARTS FOR YOUR MODEL 1000-0 AND 1010-1 HAND LAWNMOWER

WHEN ORDERING REPAIR PARTS, ALWAYS GIVE THE FOLLOWING INFORMATION AS SHOWN IN THIS LIST:

- |                     |                      |
|---------------------|----------------------|
| 1. THE PART NUMBER. | 3. The MODEL NUMBER. |
| 2. THE PART NAME.   | 4. The NAME of item. |

Your Mower is right hand (R.H.) or left hand (L.H.) as you push.

Do not use Key Numbers when ordering Repair Parts, always use Part Numbers.

### PARTS LIST


Key No.	Part No.	Description	Key No.	Part No.	Description
1	10	Trunnion .....	36	1110-24-18	Drive Wheel Less Tire.....
2	2624-18	Spacer .....	37	142	*Cotter Pin ( $\frac{1}{8}$ x $\frac{3}{8}$ ).....
3	3603-55-18	Handle Brace—16" .....	38	2674-16-17	Hub Cap.....
3	3603-43-18	Handle Brace—18" .....	39	1650-21	Retaining Ring.....
4	1511-7	*Screw (#10-32 x $\frac{3}{8}$ Rd. Hd. Self Tap)	40	141	*Washer ( $\frac{3}{8}$ x $1\frac{1}{4}$ ).....
5	3622-28-17	Cover Plate .....	41	428	Pinion Gear—L. H. ....
6	1523-3	*Screw (#10 x $\frac{3}{8}$ Ph. Hd. Sht. Mtl.).....	42	109	Felt Washer.....
7	1689-3	Grass Catcher Clip .....	43	323	Pawl.....
8	169	*Bolt ( $\frac{3}{8}$ -18 x $2\frac{1}{2}$ Sq. Hd.).....	44	3601-75-17	Gear Housing—L. H. ....
9	1509-13	*Bolt ( $\frac{3}{8}$ -18 x $2\frac{1}{4}$ Hx. Hd.).....	45	52	*Nut ( $\frac{3}{8}$ -24 Semi-Fin. Hex.).....
10	70	*Nut ( $\frac{3}{8}$ -18 Hex).....	46	11	Trunnion.....
11	2117-15-18	Handle Shaft.....	47	451	Screw (Cutter Bar Adj.).....
12	67	Nut ( $\frac{1}{4}$ -20 Hex).....	48	453	Screw (Rear).....
13	1664-2	Cross Handle .....	49	455	Screw (Front).....
14	165	*Bolt ( $\frac{1}{4}$ -20 x $1\frac{3}{4}$ carriage).....	50	2134-9-17	Cutter Bar—16".....
15	117	*Screw (#10-32 x $\frac{3}{8}$ Rd. Hd. Sems).....	50	2134-6-17	Cutter Bar—18".....
16	116	*Nut (#10-32 Sq.).....	51	159	*Washer ( $\frac{3}{8}$ x $\frac{3}{8}$ ).....
17	1112-17-17	Spacer Tube Ass'y—16".....	52	1609-80-17	Roller Bracket.....
17	1212-14-17	Spacer Tube Ass'y—18".....	53	171	Bracket Hook.....
18	88	*Screw (#6 x $\frac{1}{4}$ Self Tap Ph. Hd.).....	54	160	*Bolt ( $\frac{3}{8}$ -18 x $1\frac{1}{8}$ Carriage).....
19	1605-151	Name Plate—16".....	55	757	*Washer ( $\frac{3}{8}$ x $\frac{3}{4}$ ).....
19	1605-152	Name Plate—18".....	56	556-16	Roller—16".....
20	17	*Rivet ( $\frac{3}{8}$ x $\frac{3}{8}$ Rd. Hd).....	56	556-18	Roller—18".....
21	1629-28-17	Retainer .....	57	1129-46R-17	End Plate with Trunnions—R. H. ....
22	104	Felt Washer.....	58	1601-19R-17	Pinion Housing—R. H. ....
23	106	Felt Retainer .....	59	3601-74-17	Gear Housing—R. H. ....
24	3	Bearing.....	60	425	Pinion Gear—R. H. ....
25	149	*Nut ( $\frac{3}{8}$ -24 Jam).....	61	72	Wrench.....
26	1076	*Lockwasher ( $\frac{3}{8}$ ).....	62	1108-60-18	Drive Wheel Ass'y With Tire.....
27	154	*Washer ( $\frac{3}{8}$ x $\frac{3}{8}$ ).....	63	1129-90R-17	End Plate Ass'y—R. H. ....
28	1129-46L-17	End Plate with Trunnions—L. H. ....		1129-90L-17	End Plate Ass'y—L. H. ....
29	2135-16-17	Reel Ass'y—16".....	64	1129-63	Pawl & Pinion Gear Ass'y—L. H. ....
29	2135-17-17	Reel Ass'y—18".....	65	1129-64	Pawl & Pinion Gear Ass'y—R. H. ....
30	9	*Rivet ( $\frac{3}{8}$ x $1\frac{1}{32}$ Rd. Hd.).....	Assemblies Not Illustrated		
31	1629-9-17	Retainer.....		3111-18R-17	End Plate Ass'y—R. H. ....
32	1601-19L-17	Pinion Housing—L. H. ....			Less Gear Housing and Axle.....
33	340	Axle.....		3111-18L-17	End Plate Ass'y—L. H. ....
34	137	Bearing .....			Less Gear Housing and Axle.....
35	2619-21	Tire .....		0611-213	Operating Instructions.....

For Illustration—See Page 2

\*Standard Hardware item—may be purchased locally

## SETTING UP


1. Attach handle brace (1).
2. Attach handle brace spacer and handle with bolts and tighten nuts (2).
3. Attach cover plate and grass catcher clip with screws (3).
4. Turn down grass catcher hooks if grass catcher is used (4).



## ADJUSTMENTS

### TO TIGHTEN CUTTER BAR ADJUSTMENT

1. Loosen top nut (5) one quarter turn.
2. Tighten lower nut (6).
3. Bolts (7 & 8) must be tight after adjustment.




### SILENT YARDMAN PAPER TEST.

1. Insert strip of paper approx. 2" wide.
2. Turn reel slowly away from cutter bar with wheels off ground.
3. Adjust cutter bar so that reel blades drag on paper without tearing it.

### TO CHANGE MOWER FROM HIGH TO LOW CUT

1. Remove hub cap.
2. Remove axle and wheel.
3. HIGH CUT— $1\frac{3}{8}$  to  $2\frac{1}{4}$  in.  
Axle located in hole 1 and dowel pin in hole 4.  
MEDIUM CUT— $\frac{3}{4}$  to  $1\frac{1}{8}$  in.  
Axle located in hole 2 and dowel pin in hole 5.  
LOW CUT— $\frac{3}{8}$  to 1 in.  
Axle located in hole 3 and dowel pin in hole 6.
4. Attach wheel, axle and nut.
5. Be sure dowel pin seats in side plate hole.
6. Replace hub cap.
7. Adjust roller for height of cut and to keep chassis level.



### TO ADJUST HEIGHT OF CUT

1. Loosen both roller hanger bolts.
2. Raise or lower roller to desired cut.
3. Set both sides of roller at same height and tighten nuts.
4. If additional adjustment is desired, change bolt location.

## LUBRICATION

1. Seals on all bearings, hold dirt out and grease in. No further lubrication is required until mower is sharpened.
2. Oil Roller Bearing once or twice a year.